This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

PAT-NO:

JP359126565A

DOCUMENT-IDENTIFIER: JP 59126565 A

TITLE:

DEVELOPER STORAGE CONTAINER

PUBN-DATE:

July 21, 1984

INVENTOR-INFORMATION:

NAME

KASAMURA, TOSHIRO SASAKI, NOBUKAZU

ASSIGNEE-INFORMATION:

NAME

COUNTRY

CANON INC

N/A

APPL-NO:

JP58001569

APPL-DATE:

January 8, 1983

INT-CL (IPC): G03G015/08, G03G015/01

ABSTRACT:


PURPOSE: To prevent a developer cartridge from being inserted into a different developing device by mistake by arranging the 1st and the 2nd projections so that part of the 1st projection and the 2nd projection are at different positions in the insertion direction of the developer storage container.

CONSTITUTION: Two projections 35 and 36 of the developer cartridge 34 which contains a developer in, for example, sepia color are provided to the flange


34c of the rear end part of the cartridge at positions


which are different in the insertion directions B of the cartridge. When the cartridge is inserted into the developing device with its opening 34d up, the positioning projection 35 and color discriminating projection 36 engage with recessed parts 24" and 25' of a cover 23. Consequently, the developer cartridge is prevented from being inserted into an improper developing device by mistake.

COPYRIGHT: (C) 1984, JPO&Japio




-489-





-490-



-491-

